



www.e-props.fr

# CS GLORIEUSE for ROTAX 912 to 915iS

## Inflight Variable Pitch Constant Speed Propellers

Full Carbon with Titanium Leading Edge Protection

For Rotax 912, 912S, 912ULS, 912iS, 914, 915iS: tractor (CW), up to 157 hp

Design following CS-P standards / EASA certification in progress

Available in 7 different diameters: from 160 to 190 cm / from 63" to 74,8"

Hydraulic actuator with electronic management

Ultra-fast regulation : max / min pitch in 3 sec

Pitch variation : max. range 16° (20° in option)

Max RPM [at propeller] = 2600

Moment of Inertia = 2600 kg.cm<sup>2</sup> [for Φ 170 cm]

TBO (Time Between Overhaul) = 2000 hours

Carbon Spinners : 13 diameters

Carbon Spacers : from -10 to + 170 mm

**Ultra-Light:** 3 blades + hub + spacer + spinner + governor & regulator =

**only 4 kg / 8,8 lb**



E-Props guarantee [Satisfied or Your Money Back during 6 Months](#)

\* E-Props : high performance due to profiles optimization, using evolutionary algorithm (metaheuristics) & use of top materials (Carbon + Titanium) \*

**E-PROPS : Light is Right**